

Serial No.: 10/802,118
Group Art Unit: 2633
Examiner: Leslie C. Pascal

Amendment to the Claims

1 (Canceled). Please cancel claim 1.

2 (Canceled). Please cancel claim 2.

3 (Original). An optical regulator assembly comprising:
a plurality of optical channel regulators, each optical channel regulator comprising:
an electrically variable optical attenuator;
a tapped optical coupler;
an optical detector; and
a comparator; and
a microprocessor, operable to:
receive the electrical signal representing the attenuated optical signal from each of
the plurality of optical channel regulators;
generate a plurality of reference signals responsive to the electrical signals; and
provide a reference signal to the comparator in each of the plurality of optical
channel regulators.

4 (Original). The optical channel regulator of claim 3, wherein each optical channel regulator
further comprises:
a second tapped optical coupler receiving an input optical signal, the second tapped
optical coupler providing substantially all of the input optical signal as the optical signal received
by the electrically variable optical attenuator and providing a remaining portion of the input
optical signal as a tapped output; and
a second optical detector receiving the tapped output from the second tapped optical
coupler and providing an electrical signal representing the input optical signal.

Serial No.: 10/802,118
Group Art Unit: 2633
Examiner: Leslie C. Pascal

5 (Original). An optical channel regulator assembly comprising:
a plurality of optical channel regulators, each optical channel regulator comprising:
an electrically variable optical attenuator;
a tapped optical coupler;
an optical detector; and
a comparator; and
a microprocessor, operable to:
receive the electrical signal representing the input optical signal from each of the plurality of optical channel regulators;
generate a plurality of reference signals responsive to the electrical signals; and
provide a reference signal to the comparator in each of the plurality of optical channel regulators.

6 (Original). The optical channel regulator of claim 5, wherein each optical channel regulator further comprises:
a second tapped optical coupler receiving an input optical signal, the second tapped optical coupler providing substantially all of the input optical signal as the optical signal received by the electrically variable optical attenuator and providing a remaining portion of the input optical signal as a tapped output; and
a second optical detector receiving the tapped output from the second tapped optical coupler and providing an electrical signal representing the input optical signal.

Serial No.: 10/802,118
Group Art Unit: 2633
Examiner: Leslie C. Pascal

7 (Original). A multiple channel wavelength division multiplexed communication system comprising:

- a plurality of transmission channels;

- a plurality of optical regulators operable to receive a plurality of optical signals from said plurality of transmission channels, each optical regulator comprising:

 - an electrically variable optical attenuator;

 - a tapped optical coupler;

 - an optical detector; and

 - a comparator;

- a first microprocessor, operable to:

 - receive an electrical signal representing the attenuated optical signal from each of the plurality of optical regulators;

 - generate a plurality of reference signals responsive to the electrical signals; and

 - provide a reference signal to the comparator in each of the plurality of optical regulators;

 - an optical combiner operable to receive a plurality of said attenuated signals;

 - a first optical amplifier operable to receive an output signal from said optical combiner;

 - a second optical amplifier operable to receive an output signal from said first optical amplifier;

 - a third optical amplifier operable to receive an output signal from said second optical amplifier;

 - an optical demultiplexer operable to receive an output signal from said third optical amplifier and recover said plurality of optical signals;

- a plurality of optical regulators operable to receive a plurality of optical signals from said optical demultiplexer, each optical regulator comprising:

 - an electrically variable optical attenuator;

 - a tapped optical coupler;

 - an optical detector; and

 - a comparator;

132005RE1

Page 4

Serial No.: 10/802,118
Group Art Unit: 2633
Examiner: Leslie C. Pascal

a second microprocessor, operable to:

- receive the electrical signal representing the input optical signal from each of the plurality of optical regulators;
- generate a plurality of reference signals responsive to the electrical signals; and
- provide a reference signal to the comparator in each of the plurality of optical regulators; and
- a plurality of receive channels operable to receive a plurality of optical signals from said plurality of optical regulators.

8 (Original). The optical channel regulator of claim 7, wherein each optical channel regulator further comprises:

- a second tapped-optical coupler receiving an input optical signal, the second tapped optical coupler providing substantially all of the input optical signal as the optical signal received by the electrically variable optical attenuator and providing a remaining portion of the input optical signal as a tapped output; and

- a second optical detector receiving the tapped output from the second tapped optical coupler and providing an electrical signal representing the input optical signal.